




FAB-HGT-6A1 Fiber Termination Box-6 Cores



Description:

FAB-HGT--6A fiber access termination box is able to hold up to 6 subscribers. It is used as a termination point for the feeder cable to connect with drop cable in FTTx network system. It integrates fiber splicing, splitting, distribution, storage and cable connection in one solid protection box.

Features:

1. Water-proof design with IP-66 Protection level.
2. Integrated with splice cassette and cable management rods. Manage fibers in a reasonable fiber radius condition.
3. Easy to maintain and extend the capacity. Fiber bend radius control more than 40mm.
4. Suitable for the fusion splice or mechanical splice. 1*4 Splitter can be installed as an option.
5. Efficient cable management.
6. 6 ports cable entrance for drop cable.

Configuration:



Material	Size	Max Capacity		Empty Weight	Loaded Weight	Color
PC+ABS	A*B*C(mm) 186*116*41	SC 6 Ports	LC 12 Ports	0.8kg	1.3kg	Light Gray

How to order a Fiber Termination Box?

Model Rules: FAB-HGT-6-A-XX-XX

Model	Capacity	Type	XX: Adapter	XX: Pigtail
FAB	6	A	SC: SC/UPC AS: SC/APC LC: LC/UPC AL: LC/APC	SC: SC/UPC AS: SC/APC LC: LC/UPC AL: LC/APC